66

- **63**. The system of claim **57** wherein each such signal-processing channel means further comprises:
  - means for determining energy contributed to said brainwave signal over a predefined time interval due to components lying within said associated predefined 5 range of frequencies.
- **64**. The system of claim **57** wherein said output-measure-determining means comprises a summer.
- **65**. A system adapted to measure in a human subject a state along a continuum relating to alertness, drowsiness, <sup>10</sup> sleep, unconsciousness, or anesthesia comprising:
  - means for acquiring a brain-wave signal including rhythmic components from the subject;
  - means for selecting components of said brain-wave signal lying in a predetermined range of frequencies including frequencies above 30 Hz; and
  - means responsive to components of said signal corresponding to frequencies lying in said range for producing an output-measure signal indicative of said state of the subject;
  - said means for producing said output-measure signal being adapted to modify its response when artifact is present in said brain-wave signal.

- 66. The system of claim 65 wherein:
- said means for producing said output-measure signal causes said output-measure signal to change in a first direction when said state of the subject approaches alertness; and
- said means for producing said output-measure signal causes said output-measure signal to change in said first direction responsive to presence of artifact in said brain-wave signal.
- 67. The system of claim 65 wherein:
- said means for producing said output-measure signal causes said output-measure signal to change in a first direction when said state of the subject deviates from alertness; and
- said means for producing said output-measure signal to change in a direction opposite from said first direction responsive to presence of artifact in said brain-wave signal.

\* \* \* \* \*